

# STATICO

Static Control & Cleanroom Products

## S5100 & 5300

## Description

Clear Anti Static tape is designed for general applications in static free workstations. The product meets decay rate of MIL-B-81705, and is available on 1" Core (S5100 Series) & 3" Core (S5300 Series).



#### S5100 Series

Clear Anti Static Tape on 1" Paper Core, 36 Yards (33 Meters) Long. Available in 1/2" (12mm), 3/4" (18mm), & 1" (24mm) wide.

#### S5300 Series

Clear Anti Static Tape on 3" Paper Core, 72 Yards (66 Meters) Long. Available in 1/2" (12mm), 3/4" (18mm), 1" (24mm), & 2" (48mm) wide rolls.

#### Specifications

<b>Adhesion To Steel</b>	40 oz./inch
<b>Tensile Strength</b>	25 lb./inch
<b>Elongation</b>	20%
<b>Backing</b>	Cellulose film
<b>Adhesive</b>	Rubber-Based, Non-Staining
<b>Surface Resistivity</b>	9.8X10E9 ohms/sq.
<b>Application Temperature</b>	50-130°
<b>Thickness</b>	2.4 mils
<b>Charge Decay Time</b>	0.12 (Seconds)

#### NOTES

STATEMENTS, TECHNICAL INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED ON TESTS WE BELIEVE TO BE RELIABLE BUT THEY ARE NOT TO BE CONSTRUED IN ANY MANNER AS WARRANTIES EXPRESSED OR IMPLIED. THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR HIS INTENDED USE AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

This product should be kept away from direct exposure to sunlight and must be stored in a ventilated storage environment with temperature of 68° F (20° C).